

Philips
Composite A/V to scart
cable

1,5 m

Composite A/V

SWV3255



Turn up your viewing experience

with this audio/video cable

Depend on this cable to take your components to optimum performance. It offers the best connection for transferring audio/video signals between your components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimize signal

Protects against signal loss

- Copper braided reinforced aluminum shielding

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

Composite A/V to scart cable
1,5 m Composite A/V

Specifications

Packaging

- EAN/UPC/GTIN: 87 10895 93384 1
- Quantity: 1
- Gross Weight: 0.234 kg
- Tare Weight: 0.063 kg
- Net Weight: 0.170 kg
- Length: 18.00 cm
- Width: 17.50 cm
- Height: 3.00 cm

Inner Carton

- EAN/UPC/GTIN: 1.190
- Quantity: 4
- Gross weight: 1.190 kg
- Tare weight: 0.250 kg

- Net weight: 0.940 kg
- Length (cm): 18.20 cm
- Width (cm): 17.70 cm
- Height (cm): 12.20 cm

Outer Carton

- EAN/UPC/GTIN: 87 10895 96121 9
- Quantity: 24
- Gross weight: 7.110 kg
- Tare weight: 1.494 kg
- Net weight: 5.616 kg
- Length (cm): 54.50 cm
- Width (cm): 30.00 cm
- Height (cm): 29.50 cm

SWV3255/10

Product highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-08-25

Version: 5.1.10

12 NC: 9082 100 06264
EAN: 87 10895 93384 1

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com